



2nd FLOOR FRAMING PLAN
1/8" = 1'-0"

FRAMING NOTES:
1. ALL ELEVATIONS ARE BASED ON FINISH FLOOR = 106'-0".
2. BRIDGING NOT SHOWN FOR CLARITY. REFER TO GENERAL NOTES.
3. MEMBER CONNECTION SHALL SATISFY THE LATEST OSHA ERECTION REQUIREMENTS.
4. REFER TO 1024 FOR THERMOBLOCK WALL REINFORCING. REFER TO SHEET S4.1 FOR WALL PLAN.

FLOOR JOIST PLACEMENT
FLOOR JOIST MAY BE ADJUSTED A MAXIMUM OF 6 INCHES TO ALLOW FOR MECHANICAL/PLUMBING PLACEMENTS. NO TWO ADJACENT JOISTS MAY BE ADJUSTED UNLESS IN THE SAME DIRECTION. ALL JOIST ADJUSTMENTS MUST BE APPROVED BY ENGINEER PRIOR TO WELDING IN PLACE.

LEGEND

— THERMOBLOCK UNITS BELOW FRAMING LEVEL
— THERMOBLOCK ICF WALL
— THERMOBLOCK ICF WALL BELOW FRAMING LEVEL ONLY
— JOIST FRAMING
— STEEL BEAM (+X DENOTES POSITIVE VERTICAL CAMBER WHERE REQUIRED)